





31 Korai str., GR183 45 Moschato, Greece Tel: +30 2104833273 Web: <u>www.inquality.gr</u> Email: <u>info@inquality.gr</u>

The new FCB: Checkweighing and portioning scale with up to three interfaces

Features

- Standardised, convenient KERN concept of operation, consistency across products in terms of design, menu structure, button functions, interface connection and interface protocol
- Compact size, practical for small spaces
- Industry 4.0: Data and control commands can be exchanged through the KERN Universal Port using one interface, which can be connected to the housing, or through three parallel interfaces using the KUP Extension box. The following interfaces are available as an option: RS-232, USB, Ethernet, WiFi, Bluetooth
- Data query and remote control of the balance using a computer or CRM/ERP systems using the KERN Communication Protocol
- For further information on KUP and KCP see page 20/21
- High mobility: Thanks to battery operation/ rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department, etc.)

- Weighing with tolerance range (checkweighing): Input of two upper and two lower limit values through four arrow keys. An audible and visual signal assists with the portioning, dispensing or grading
- Summation of weight values
- · Protective working cover included with delivery

Technical data

- Backlit LCD display, digit height 24 mm
- Dimensions weighing surface, stainless steel, W×D 252×225 mm
- + Overall dimensions W×D×H 322×267×91 mm
- Optional battery operation, 4×1.5 V AA not included in scope of delivery, operating time up to 20 h
- Net weight approx. 3,8 kg
- Permissible ambient temperature 0 °C/40 °C

Accessories

- Protective working cover, scope of delivery
 5 items, KERN YBA-A14S05, € 44,-
- Signal lamp for visual support of weighing with tolerance range. connection is only possible in combination with KUP-01 (RS 232 interface), KERN CFS-A03, € 310,-
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01, € 35,-
- External data interface RS-232, interface cable included, KERN KUP-01, € 60,-
- External data interface USB, interface cable included, KERN KUP-03, € 75,-
- Interface adapter Ethernet,
 KERN KUP-04, € 115,-
- Interface adapter WiFi, KERN KUP-05, € 75,-
- Bluetooth interface adapter, KERN KUP-06, € 99,-
- ■ Extension box for connecting up to three interfaces in parallel, KERN KUP-13, € 75,-
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD									OPTION											
	氘	KCP	GLP		%	C	-√+ ⊙ ?)	^-		В			Ĩ	• 688. •	\leftarrow	8		- a		DAkkS
CAL EXT	KUP	PROTOCOL	INTERN	PCS	PERCENT	UNIT	TOL	MOVE	BATT	MULTI	DMS	1 DAY	ET	RS 232	USB	BT 4.0	WIFI	LAN	ACCU	+3 DAYS

Model	Weighing capacity [Max] kg		Readability [d]	Reproducibility	Linearity	Smallest part weight (Normal)	Resolution	Price excl. of VAT ex works	Options DAkkS Calibr. Certificate DAkkS		
KERN			g	g	g	g/piece	Points	€	KERN	€	
FCB 6K-5	NEW	6	0,05	0,05	± 0,15	0,5	120.000	330,-	963-128	118,-	
FCB 8K0.1	NEW	8	0,1	0,1	± 0,3	1	80.000	275,-	963-128	118,-	
FCB 12K-4	NEW	12	0,1	0,1	± 0,3	1	120.000	330,-	963-128	118,-	
FCB 12K1	NEW	12	1	1	± 3	10	12.000	220,-	963-128	118,-	
FCB 30K-4	NEW	30	0,2	0,2	± 0,6	2	150.000	330,-	963-128	118,-	
FCB 30K1	NEW	30	1	1	± 3	10	30.000	260,-	963-128	118,-	

🔤 New model