



31 Korai str., GR183 45 Moschato, Greece

Tel: +30 2104833273

Web: www.inquality.gr

Email: info@inquality.gr

7 All-round bench scale, protected by stainless steel and IP65 rating, verification optional

Features

- **1** Ideal for the ever-increasing hygienic requirements in the food, pharmaceutical and chemical industries
- Your support in a HACCP-compliant quality system
- **2** Ideal for the robust industrial applications
- **3** Protection against dust and water splashes IP65 (only when using rechargeable battery pack)
- High mobility: thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations (kitchens, sales offices, cafeterias, food industry laboratories, etc.)
- Thanks to the stainless steel design of the housing and platform with smooth surface, the scale is rust-free and easy to clean
- Recessed grips on the underside of the scale for easy transportation

Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 233x193 mm
- Overall dimensions WxDxH 243x300x127 mm
- Rechargeable battery pack integrated, as standard, operating time up to 50 h without backlight, charging time approx. 12 h
- Net weight approx. 4,0 kg
- Permissible ambient temperature: -10 °C/40 °C

Accessories

- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions WxDxH 400x300x45 mm, KERN RFS-A02, € 75,-

STANDARD: CAL EXT, UNIT, IP 65, ACCU, MULTI, DMS, 1 DAY

OPTION: DAKKS +3 DAYS

FACTORY: M +3 DAYS FFN-M

Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Price excl. of VAT ex works €	Options			
						Verification M DAKKS KERN €	DAKKS Calibr. KERN €	Certificate €	
KERN FFN 1K-4N	1,5	0,2	-	-	325,-	-	-	963-127	98,-
FFN 3K0.5IPN	3	0,5	-	-	325,-	-	-	963-127	98,-
FFN 6K1IPN	6	1	-	-	325,-	-	-	963-128	118,-
FFN 15K2IPN	15	2	-	-	325,-	-	-	963-128	118,-
FFN 25K5IPN	25	5	-	-	325,-	-	-	963-128	118,-

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

FFN 1K-4NM	1,5	0,5	0,5	10	340,-	965-227	65,-	963-127	98,-
FFN 3K1IPM	3	1	1	20	340,-	965-227	65,-	963-127	98,-
FFN 6K2IPM	6	2	2	40	340,-	965-228	84,-	963-128	118,-
FFN 15K5IPM	15	5	5	100	340,-	965-228	84,-	963-128	118,-
FFN 25K10IPM	25	10	10	200	340,-	965-228	84,-	963-128	118,-