



31 Korai str., GR183 45 Moschato, Greece

Tel: +30 2104833273

Web: www.inquality.gr

Email: info@inquality.gr

6

High resolution bench scale with large weighing range and robust stainless steel weighing plate

Features

- Thanks to the high resolution of up to 360.000 points it is ideal for high-precision weighing in the industrial field
- Robust plastic die-cast housing: maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- Industry 4.0: The integrated KERN Universal Port (KUP) allows the connection of external KUP interface adapters such as RS-232, USB, Bluetooth, WiFi, Analogue, Ethernet etc. The outstanding advantage here is that the KUP interface adapters are simply plugged in, i.e. retrofitting interfaces is conveniently possible without opening the scale housing or complicated installation. The interface adapters enable convenient transmission of weighing data to networks, PCs, smartphones, tablets, laptops, printers etc. In addition, control commands and data inputs can also be sent to the scale via the connected devices.
Tip: with the KERN KUP-13 extension box, up to three KUP interface adapters can be operated in parallel on the scale
- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Freely programmable weighing unit, e.g. display direct in special units such as length of wire g/m, surface weight g/m², or else
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard
- Protective working cover included with delivery



Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 340x240 mm
- Overall dimensions WxDxH, 350x390x120 mm
- Optional battery operation, 4x1.5 V AA not included in scope of delivery, operating time up to 20 h
- Net weight approx. 7 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN FKB-A02S05, **€ 44,-**
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01, **€ 35,-**
- External data interface USB, interface cable included, KERN KUP-03, **€ 75,-**
- External data interface RS-232, interface cable included, KERN KUP-01, **€ 60,-**
- Interface adapter Ethernet, KERN KUP-04, **€ 115,-**
- Interface adapter WiFi, KERN KUP-05, **€ 75,-**
- Bluetooth interface adapter, KERN KUP-06, **€ 99,-**
- Extension box for connecting up to three interfaces in parallel, KERN KUP-13, **€ 75,-**
- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions WxDxH 400x300x45 mm, KERN RFS-A02, **€ 75,-**
- Further details, plenty of further accessories and suitable printers see *Accessories*

1 Particularly practical: thanks to the large weighing ranges and compact dimensions, you can accurately weigh heavy loads in the most restricted of spaces. Useful for determining very small weight differences, such as, for example, gas wastage, abrasion of mechanical parts, rock samples, minerals, druses, silver etc.

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Reproducibility g	Linearity g	Smallest part weight (Normal) g/piece	Resolution Points	Price excl. of VAT ex works €	Options	
								DAkKS Calibr. DAKKS KERN	Certificate €
FKB 6K0.02	6	0,02	0,04	± 0,1	0,2	300.000	520,-	963-128	118,-
FKB 8K0.05	8	0,05	0,05	± 0,15	0,5	160.000	490,-	963-128	118,-
FKB 16K0.05	16	0,05	0,1	± 0,25	0,5	320.000	550,-	963-128	118,-
FKB 8K0.1	8	0,1	0,1	± 0,3	1	80.000	360,-	963-128	118,-
FKB 16K0.1	16	0,1	0,1	± 0,3	1	160.000	495,-	963-128	118,-
FKB 15K0.5	15	0,5	0,5	± 1,5	10	30.000	385,-	963-128	118,-
FKB 36K0.1	36	0,1	0,2	± 0,5	1	360.000	550,-	963-128	118,-
FKB 36K0.2	36	0,2	0,4	± 1	2	180.000	550,-	963-128	118,-
FKB 65K0.2	65	0,2	0,4	± 1	2	325.000	525,-	963-129	146,-
FKB 30K1	30	1	1	± 3	20	30.000	340,-	963-128	118,-
FKB 65K1	65	1	1	± 3	20	65.000	360,-	963-129	146,-



FOB



FOB-NL

7 Compact stainless steel balance with large weighing range

Features

- FOB: Innovative weighing with tolerance range (Checkweighing): The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning, dosing and grading
- FOB-NL: Protection against dust and water splashes IP67 (only when using battery)
- Thanks to the stainless steel design of the housing and platform with smooth surface, the scale is rust-free and easy to clean
- Increased protection against humidity through waterproof silicone sealing of the load cell, electronics and soldering joints

- Your support in a HACCP-compliant quality system
- Ideal for the increased hygienic requirements in the food industries
- High mobility: Thanks to battery operation/rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Secure and non-slip positioning with rubber feet

Accessories

- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions W×D×H 400×300×45 mm, KERN RFS-A02, € 75,-

FOB

- Protective working cover, scope of delivery: 5 items, KERN FOB-A05S05, € 44,-
- Internal rechargeable battery pack, operating time up to 24 h without backlight, charging time approx. 8 h, KERN FOB-A07, € 60,-

FOB-NL

- Protective working cover, scope of delivery 5 items, KERN FOB-A13S05, € 44,-
- External mains adapter, KERN YKA-29, € 43,-

STANDARD



OPTION



STANDARD



OPTION



KERN	FOB 1.5K0.5	FOB 3K1	FOB 6K2	FOB 3K-4NL	FOB 7K-4NL*	FOB 10K-3NL*	FOB 30K-3NL*
Weighing capacity [Max] kg	1,5	3	6	3	5 7,5	8 15	16 30
Readability [d] g	0,5	1	2	0,2	0,5 1	1 2	2 5
LCD display backlight, digit height		yes, 20 mm		no, 25 mm		yes 25 mm	
Dimensions of weighing plate W×D mm		175×165			252×200		
Overall dimensions W×D×H mm		235×175×55	243×183×54		285×255×90		
Power supply included with delivery		Power supply			Battery, 4×1.5 V AA operating time up to 48 h		
Net weight	1,8 kg		2,0 kg			3,8 kg	
Permissible ambient temperature		5 °C – 35 °C			5 °C – 35 °C		
Price, excl. of VAT, ex works, €	240,-	240,-	240,-	330,-	295,-	295,-	295,-
Option DAKkS Calibr. Certificate	963-127, € 98,-	963-127, € 98,-	963-128, € 118,-	963-127, € 98,-	963-128, € 118,-	963-128, € 118,-	963-128, € 118,-

*Multi-division balance, with increasing or decreasing load, it switches automatically to the next largest or smallest weighing range [Max] and readout [d].