



Application examples

- Small industrial scale for pharmacies
  - Hand mixtures of tea, coffee, chocolates
  - Portioning of dough, meat, fish, poultry, mixed salads in cafeterias etc.
  - Mobile weighing of freshly picked fruit on site
  - Checkweigher in supermarkets
  - High-precision industrial applications, piece counting or stock-taking
- Note: Official verification is mandatory for commercial trade

6

## Checkweighing and portioning scale, verification optional

### Features

- Compact size, practical for small spaces
- High mobility: thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations (production, warehouse, dispatch department, etc.)
- Weighing with tolerance range (checkweighing): a visual and audible signal helps with portioning, dispensing or grading
- Summation of weight values
- Protective working cover included with delivery

### Technical data

- Large backlit LCD display, digit height 24 mm
- Dimensions weighing surface, stainless steel, WxD 295x225 mm
- Overall dimensions WxDxH 315x350x125 mm
- Net weight approx. 3,0 kg
- Permissible ambient temperature 0 °C/40 °C

### Accessories

- Protective working cover, scope of delivery: 5 items, KERN CFS-A02S05, € 44,-
- Internal rechargeable battery pack, operating time up to 90 h without backlight, charging time approx. 12 h, KERN GAB-A04, € 42,-
- **1** Signal lamp for visual support of weighing with tolerance range, KERN CFS-A03, € 310,-
- **2** Y-cable for parallel connection of two terminal devices to the RS-232 interface on the scale, e.g. signal lamp and printer, KERN CFS-A04, € 38,-
- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions WxDxH 400x300x45 mm, KERN RFS-A02, € 75,-
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



FACTORY



Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Smallest part weight (Normal) g/piece	Price excl. of VAT ex works €	Options			
							Verification M KERN	€	DAkKS KERN	Certificate €
GAB 6K0.05N*	6	0,05	-	-	0,5	395,-	-	-	963-128	118,-
GAB 12K0.1N*	12	0,1	-	-	1	395,-	-	-	963-128	118,-
GAB 30K0.2N*	30	0,2	-	-	2	395,-	-	-	963-128	118,-
Multi-division balance, with increasing or decreasing load, it switches automatically to the next largest or smallest weighing range [Max] and readout [d].										
GAB 6K1DNM*	3   6	1   2	1   2	20	2	310,-	965-228	84,-	963-128	118,-
GAB 15K2DNM*	6   15	2   5	2   5	40	5	310,-	965-228	84,-	963-128	118,-
GAB 30K5DNM*	15   30	5   10	5   10	100	10	310,-	965-228	84,-	963-128	118,-

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

**1** \* ONLY WHILE STOCKS LAST