



## Ideal for food industry, thanks to its IP65 protection and special checkweighing display, verification optional

7

### Features

- Ideal for the increased hygienic requirements in the food industries
- Your support in a HACCP-compliant quality system
- **1** Protection against dust and water splashes IP65 (only when using rechargeable battery pack)
- Very fast display: steady weight values within 2 s
- **2** Second display on the back of the balance
- Compact size, practical for small spaces
- **3** Innovative weighing with tolerance range (Checkweighing): The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning, dosing and grading

### Accessories

- High mobility: thanks to rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Recessed grips on the underside of the scale for easy transportation
- Protective working cover included with delivery

### Accessories

- Protective working cover, scope of delivery 5 items, KERN RFB-A01S05, **€ 44,-**
- Internal rechargeable battery pack, operating time up to 50 h without backlight, charging time approx. 12 h, KERN WTB-A01N, **€ 38,-**
- **4** Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions WxDxH 400x300x45 mm, KERN RFS-A02, **€ 75,-**

### Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, WxD 263x203 mm
- Overall dimensions WxDxH 286x316x126,5 mm
- Net weight approx. 3,2 kg
- Permissible ambient temperature -10 °C/40 °C

STANDARD					OPTION		FACTORY	
							WTB-NM	

Model	Weighing capacity [Max] kg	Readability [d] g	Verification value [e] g	Minimal load [Min] g	Price excl. of VAT ex works €	Verification		Options	
						KERN	€	DAkkS KERN	Certificate €
<b>KERN</b>									
<b>WTB 1K-4N</b>	1,5	0,2	-	-	<b>285,-</b>	-	-	963-127	98,-
<b>WTB 3K-4N</b>	3	0,5	-	-	<b>285,-</b>	-	-	963-127	98,-
<b>WTB 6K-3N</b>	6	1	-	-	<b>285,-</b>	-	-	963-128	118,-
<b>WTB 10K-3N</b>	15	2	-	-	<b>285,-</b>	-	-	963-128	118,-
<b>WTB 30K-3N</b>	30	5	-	-	<b>285,-</b>	-	-	963-128	118,-

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order. The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

<b>WTB 3K-3NM</b>	3	1	1	20	<b>300,-</b>	965-227	65,-	963-127	98,-
<b>WTB 1K-4NM</b>	1,5	0,5	0,5	10	<b>300,-</b>	965-227	65,-	963-127	98,-
<b>WTB 6K-3NM</b>	6	2	2	40	<b>300,-</b>	965-228	84,-	963-128	118,-
<b>WTB 10K-3NM</b>	15	5	5	100	<b>300,-</b>	965-228	84,-	963-128	118,-
<b>WTB 30K-2NM</b>	30	10	10	200	<b>300,-</b>	965-228	84,-	963-128	118,-