

TiltIndicator™ Mounting Instructions

1- Keep the Tilt Indicator **upright** while (and after) removing the adhesive backliner, as from that point on the indicator is armed and ready to activate.

2- The Tilt Indicator should be placed low on the parcel, preferably close to an edge. That is the most solid part of a package and it helps to align the indicator upright.



Note: a TiltIndicator™ detects tilting to the left or right.

To also monitor front/back tilting: place a 2nd device on an adjacent side

3- The surface should be clean and oil-free. Press at corners and center to get a strong adhesion. When mounting the Tilt Indicator onto densely waxed or rough wood, we suggest in addition, to either use a spray adhesive for better bonding, or to staple the indicator onto to wood through the holes at the top and bottom of the indicator.

- 4- The use of an optional companion label will not only make the people handling your parcel better aware of the presence of the TiltIndicator™, but it will also explain the receiver what to do in case of activation (a red colored indicator). Companion labels are available in English, or in a multi-lingual (English/French/German/Spanish) version.



- 5- With each TiltIndicator™ you also receive a small Alert Sticker. Stick that onto the bill of lading (packing list) to remind receivers to check the TiltIndicator™ first, before signing for good receipt.

!! ATTENTION !!

If TILT INDICATOR is Red:
 → **DO NOT** refuse shipment, but
 → make a note on Bill of Lading, and
 → inspect for damage immediately.



These are general instructions. If you believe your application is different and/or have questions about (how to use) the indicator, then please do not hesitate to contact your local dealer, or contact us direct via email info@logimon.solutions or phone +31 (0)85 – 0066 082.

For additional product information, please visit www.TiltIndicator.eu