



TILT INDICATOR '3-in-1' *to monitor your valuable goods*



LOGIMON
LOGISTICS MONITORING SOLUTIONS



European distributor on behalf of:
SHOCKINDICATOR ENTERPRISE CO.,LTD

TILTINDICATOR 3in1



SPECIFICATION

Product name	TiltIndicator 3in1
Dimensions	120 x 120 x 7.7 mm
Operating temperature	-40°C ~ +60°C (-40°F ~ 140°F)
Activation angle	Activation angle : Tilt to Left 30°, 40°, 50°, 60°, 70°, 80° Tilt to Right 30°, 40°, 50°, 60°, 70°, 80° Overturn 180°
Components :	Brass beads, ABS, Polycarbonate, Semigloss Gloss Paper
Shelf life	2 years
Packing	50pcs/box

DESCRIPTION

TiltIndicator 3in1 is applied to the packaging and provides evidence of mishandling if the shipment is tilted. Providing 360° monitoring of goods that must keep upright. When the parcel has tilted, the brass balls move to the corresponding tilt angle, providing disputable evidence of mishandling. As a visual reminder to handle with care as carriers know and see the package is being monitored.

FEATURES

- △ Unique serial number & Tamper-proof
- △ Protect fragile, sensitive or calibrated goods while in-transit.
- △ Alert carriers that careful handling is mandatory – visual deterrent.
- △ Provide evidence that mishandling occurred.
- △ Enhance image with customer, restores faith in your ability to delivery product safely.

ACCESSORIES - included with each indicator:



Warning/Instruction label

Length x Width: 100 x 72 mm

1. To note the critical tilt angle for the parcel.
2. Instructions how to handle in case the brass balls show that critical tilting has happened.

ATTENTION!

This shipment is monitored with a **TILT Indicator**. Please check that indicator if excessive tilting has occurred, and follow its instructions.

Small Alert sticker

Length x Width: 72 x 20 mm.

To go onto the shipping documents, alerting the receiver to check the indicator/parcel first.

INSTRUCTIONS

1. Hold the Tiltindicator 3in1 upright and peel off the backside. This arms the indicator.
2. Attach the Tiltindicator 3in1 onto your parcel. A corner or side helps to keep it straight.
3. Write the critical (unacceptable) tilt angle on the Warning/Instruction Label and apply that close to the indicator.



If you basically want to know if your parcel has been tilted on its side, our standard TILT Indicator ($\pm 80^\circ$ angle) should be a good, cost-effective choice.



CONTACT US

+31 (0)85 - 0066 082

info@LogiMon.solutions

www.TiltIndicator.eu
www.LogiMon.solutions

Hameinde 1
7371CS Loenen Gld.
The Netherlands

Follow us on  via



Also check our Shock/Impact Indicators

V2401-3